

TRX250TM

Tried, tested & proven over 17 years working in the Australian market. Excellent breeding, built from tough DNA.



THE SPECS TRX250TM

Engine Type	229cc air-cooled OHV longitudinally mounted single-cylinder 4-stroke
Bore and Stroke	68.5 x 62.2mm
Carburation	22mm piston-valve
Ignition	CD with electronic advance
Starter	Electric with auxiliary recoil
Clutch	Automatic / Centrifugal
Transmission	5-speed with reverse
Drive	Direct rear enclosed driveshaft
Dimensions	1,905mm x 1,035mm x 1,070mm (LxWxH)
Wheelbase	1,131mm
Seat Height	793mm
Ground Clearance	152mm
Turning Radius	2.5m
Fuel Capacity	9.1 litres
Front Tyre	22 x 7-11
Rear Tyre	22 x 10-9
Front Suspension	Independent double-wishbone; 130mm of travel
Rear Suspension	Swingarm with single shock; 125mm of travel
Front Brake	Dual sealed hydraulic drum
Rear Brake	Sealed mechanical drum
Towing Capacity	225kg
Carrier Capacity	15kg (front) 30kg (back)
Max Weight Capacity	175kg*
Kerb Weight	199kg
Warranty Period	36 months

*Overseas model shown.

*Any load limits apply to standard equipment only. Modifying your ATV or SXS, using non-standard equipment, or riding on terrain that is not flat and smooth could further reduce these limits.

